



EAN code:
WDC-1: 8595188193795

Technical parameters	WDC-1
Power supply:	1x 3 V CR 2032 battery
Drained battery indicator:	yes
Control	
Communication protocol:	RFIO3
Frequency:	866–922 MHz
Repeater function:	no
Other data	
Working temperature:	-10 to +50 °C
Protection:	IP20
Colour:	black
Dimension:	25 x 75 x 16 mm
Weight:	16 g
Magnet dimension:	15 x 75 x 14 mm
Magnet weight:	12 g
Standards:	EN 60730, EN 63044, EN 301489, EN 300 220

- The Window/Door detector is used to detect opening where activation occurs when the magnet and the sensor become separated.
- Use:
 - in combination with the switching unit for automatic light control (cellar, garage, etc.).
 - by means of the Mini Bridge MB-1, detection can be displayed on your smart phone in the form of a notification; alarms are stored in the history, which is visualized in the iNELS Home app.
- Anti-tamper function: an alarm is triggered if there is an unauthorized interference to detector.
- Power supply: 1x 3 V CR 2032 battery, the battery life is around 1 year, thanks to the ability to turn off the LED indicator it is possible to extend up to 3 years.
- “Low Battery” Alerts on Your iNELS Home app.
- The detectors are compatible with switching components marked with the RFIO3 communication protocol and the Mini Bridge system components.